

**DVB-S2 & H.264/MPEG-4/MPEG-2**◆ **MODEL No.:GSR-HN4910**◆ **SPECIFICATION:**

- ✓ DVB-S & DVB-S2 Compliant.
- ✓ MPEG-2 MP@HL video decoder
- ✓ AVC/H.264 HP@L4.1 video decoder
- ✓ MPEG4 ASP supported
- ✓ Fully compliant with HDMI1.3 specification
- ✓ Video Resolution: 1080p,1080i,720p,720i,576p,576i
- ✓ USB2.0 for PVR, Time-shift and timer.
- ✓ Support MP3/ WMA, AVI/MKV/MP4/..., BMP/JPG playback.
- ✓ Blind scan, Sat scan, TP scan , NIT scan
- ✓ Max 2000 TP and 4000 Programs restore.
- ✓ DiSEqc1.0/DiSEqc1.2/ DiSEqc1.3( USALS).
- ✓ Support 7-day EPG, Teletext and Subtitle.
- ✓ Parental lock, Channel Edit, Favor edit.
- ✓ OTA 、 RS232 、 USB upgrade





## Technical specification:

**◆ Chipset and Memory:**

Processor : ALI M3510C  
Flash:4MB\8MB serial flash  
DDR: DDRII 800 64MB  
**TUNER:M3031**

**◆ Power**

Input: DC12V, 1A  
Operating:10W  
Max: 12W

**◆ Interface:**

ANT IN x1  
RCA:, CVBS x1, Audio x1  
HDMI 1.3x1  
USB2.0 port: x1  
RS232

**◆ Video Decoding**

Compliant with: MPEG-4 part10 /MPEG-2 ISO/IEC 13818,  
MPEG-4 Simple/Main/Advanced Profile@Level3(10Mbps),  
MPEG-2 Main Profile@ Main Level(15 Mbps)  
H.264 MP@L3(10Mbps),H.264 HP@L4.1 (25Mbps)  
Video Resolution: 1080p,1080i,720p,720i,576p,576i

**◆ Audio Decoding**

Compliant with: MPEG-1/2/3, AC-3, HE AAC (optional)  
Support Dolby down-mixed 2 channel (optional)

**◆ Physical**

Dimensions (W x H x D) 107x 77x 16mm  
Weight: 0.5 kg  
Temperature: 0 °C ~ +45 °C  
Humidity: 8%~95%

**◆ Accessories**

Remote Control(excluded battety)  
AV Cable  
HDMI Cable  
User Manual