


## GKA35-GT001

### Ku-band Rx Antenna



#### Main Features

- Optimized structure design, easy for field assembly and alignment
- High performance and surface precision
- Surface anti-corrosion treatment for long operation life
- Customizable logo and color
- Scale of survival wind force up to 12(dish direction fixed)
- Package suitable for air, ocean and land transportations

#### Technical Specifications

##### Mechanical

Reflector Diameter	0.35m (13.7 inch)
Antenna Type	Partial feedback
Mount Type	Ground
Segment of Reflector	1

##### Electrical

Frequency	10.7 to 12.75GHz
Antenna Gain	≥30.8 dBi
F/D Ratio	0.6

##### Environmental

Environment Temperature	-50 to 70℃ (-58 to 158°F)
Environment Humidity	5 to 95%
Operational Wind	68km/h(43mph), performance decrease@96km/h(59mph)
Survival Wind	124km/h(78mph)

#### For More Information

Please visit our website: <http://www.gospell.com> or contact our sales representative:

##### XIPOINT Overseas Sales Center

CHENZHOU XIPOINT Technology Co., Ltd

Addr.: Block F10-F13, F518 Idea Land, Baoyuan road, Bao'an Central District, Shenzhen City 518102, Guangdong Province, China

TEL: +86-755-26716112

FAX: +86-755-26716132

E\_mail: [sales@gospell.com](mailto:sales@gospell.com)

##### XIPOINT Dubai

CHENZHOU XIPOINT Technology Co., L.L.C

Addr.: Malabar Supermarket, 12 street, Maryamal Gaizi Building, #116 Deira, Dubai, The United Arab Emirates

TEL: +971-4-2324258

FAX: +971-4-2247318

XIPOINT, A GOSPELL Company.

©2017 GOSPELL Digital Technology Co., Ltd. All rights reserved.

The XIPOINT logo is trademark of GOSPELL Digital Technology Co., Ltd.

All other trademarks mentioned in this document are the property of their respective owners.

Product pictures are for reference only, XIPOINT reserves the right to modify the specifications without prior notice

